

Technical Data Sheet

Potassium Silicate Liquid				
Product Name		Potassium Silicate Liquid		
Product Code		KL-30B		
Technical Data Sheet (Properties)				
Chemical Properties				
Sr. NO	Characteristic	Unit	Specification	Test Method
1	Weight. Ratio	-	2.1 - 2.3	IS-14212:1995
2	Molar. Ratio	-	3.27 -3.58	IS-14212:1995
3	K ₂ O Content	%	9-10	IS-14212:1995
4	SiO ₂ Content	%	20-22	IS-14212:1995
5	Total Solid	%	29-30	IS-14212:1995
Physical Properties				
6	Appearance	-	Colorless Liquid	Visually
7	Baume (Degree) at 27 °C	^o Be	28-32	IS-14212:1995
8	Sp Gravity	-	1.250-1.300	IS-14212:1995

Packing, Loading & Shelf life.

Packing	50KG,100KG,250KG,300KG HDPE Drums , 1000 to 1200 KG IBC Tank Tanker loading – 10 to 30 MT
Loading – W/o Pallet	50KG,100KG,250KG,300KG – 20 to 24 MT/20FCL 1300-1400 KG IBC Tank – 22 to 25 MT/20FCL
Loading – On Pallet	50KG & 100KG – 18 to 20MT/20FCL 250KG & 300KG – 22 to 26 MT/20FCL
Shelf Life	24 Month under proper storage condition*

** Proper Storage condition: Keep container tightly closed, keep in cool, dry and ventilated place, and avoid strong acid.*